




High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



VALVE BOXES - Surface Mount ASVB

Application

- Provides easy access to all types of valves and controls that extend outside of the finished wall, but need to be protected by a fully enclosed box.

Product Features

- The depth of the valve box can be modified to meet all the valve and control requirements.
- When required, vision panels, louvers, engraved plates can be supplied, along with special holes for pipes or conduits.

ASVB Valve Box Specifications:

Box Material: Stainless Steel or Steel: 16 gage door & box

Box Door: Overlaps box, providing for a tight secure fit

Box: Fully enclosed, completely attached to frame. When required, box can be made with open back.

Box Hinge: Continuous, exposed piano hinge

Box Latch: Cylinder lock & key. Also available: screwdriver operated cam latch, allen head cam latch, spanner head cam latch, flush paddle handle, thumb turn latch

Box Finish: Stainless Steel: #4 satin polish. Steel: 5 stage iron phosphate preparation with prime coat of White alkyd baking enamel



AVAILABLE SIZES *(Special sizes available upon request)*

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
8 X 8 X 4	203 X 203 X 101	1	5	2.3
8 X 8 X 6	203 X 203 X 152	1	7	3.2
8 X 8 X 8	203 X 203 X 203	1	9	4.1
12 X 12 X 4	305 X 305 X 101	1	9	4.1
12 X 12 X 6	305 X 305 X 152	1	12	5.5
12 X 12 X 8	305 X 305 X 203	1	14	6.4

Wall opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

